



Traver Land

90+

90+ | 素色肌肤砖



90+ | 素色肌肤砖  
广东佛山禅城区绿岛国际新城90号  
欧洲工业园二期三号楼之C2  
C Area, Level 3, Building 2, European Industrial Park,  
No.60, West Langjiao Road of Foshan City,  
Guangdong Province, P.R.China

60TL20R  
600x600mm  
612TL20URD  
600x1200mm

OFF-WHITE

60TL21R  
600x600mm  
612TL21URD  
600x1200mm

SILVER GREY

60TL22R  
600x600mm  
612TL22URD  
600x1200mm

IVORY

Karst cave series has clear stripes and natural holes restored by the mold, creates a full sense of three-dimensional. It can achieve P3 anti-slip rate, making the tile surface safer.

It is made of environment-friendly materials, with four colors available. One stone has different patterns and various textures, bringing rich visual experience. It is not only suitable for paving at home, but also can be used in various commercial places and public places.



WALL-612TL20URD  
FLOOR-60TL20R



OFF-WHITE

- 60TL20R  
600x600mm
- 612TL20URD  
600x1200mm

The bright off white is pure and clean, with different hole textures and overlapping textures bringing the natural landscape into the space.

WALL:36TL20R  
FLOOR:60TL20R





FLOOR-60TL21R

SILVER GREY

60TL21R

600x600mm

612TL21URD

600x1200mm

The silver grey color has a mysterious temperament, which shows its dignity in the space. You can feel the beauty of nature without leaving home.



WALL:36TL21R  
FLOOR:60TL21R



FLOOR-612TL22URD

IVORY

60TL22R

600x600mm

612TL22URD

600x1200mm


Ivory color brings a warm feeling to people. Every detail is perfect. The texture of the cave stone is perfectly reproduced, bringing both visual and tactile enjoyment.





**PRODUCT FEATURE / SURFACE APPLICATION / INSTALLATION GUIDANCE**

--	--	--	--	--	--	--	--	--



**TECHNICAL SPECIFICATION**

MEASUREMENT AND SURFACE APPEARANCE	STANDARD PRESCRIBED VALUES	90+ VALUES	90+ VALUES
<b>Dimensions &amp; Surface Quality</b>			
Length and Width	±0.6% max.	-0.03-0.03%	-0.03-0.03%
Thickness	±5% max.	9.0-9.5mm	11.0-11.5mm
Orthogonality	±0.5% max.	-0.06-0.07%	-0.06-0.07%
Straightness of sides	±0.5% max.	-0.06-0.07%	-0.02-0.03%
Surfaces flatness	±0.5% max.	-0.05-0.07%	-0.09-0.11%
<b>Physical Properties</b>			
Water absorption	≤0.5%	≤0.5%	≤0.5%
Breaking strength	≥1300N	2265N	4031N
Bending resistance	≥35N/mm <sup>2</sup>	38N/mm <sup>2</sup>	40N/mm <sup>2</sup>
Resistance to deep abrasion	≤175mm <sup>3</sup>	Class 4	Class 4
Temperature shock resistance	No visible crack	No visible crack	Durable
Resistance to frost	No visible crack	No visible crack	No visible crack
Non-slip	R9-R11	R11	R11
Colour resistance to light	no colour changes	no colour changes	no colour changes
<b>Chemical Properties</b>			
Chemical resistance	no visible changes when subjected to chemicals	Durable	Durable
Resistance to staining	≥3	Class 5	Class 5

**PACKING DETAILS**

SIZES	SURFACE	PCS/CTN	M <sup>2</sup> /CTN	KG/CTN
600x600mm				
600x1200mm		4	1.44	31.5
		2	1.44	43

**PRODUCT FEATURE / SURFACE APPLICATION / INSTALLATION GUIDANCE**

--	--	--	--	--	--	--	--	--



**COLOURS**

	Off-white 60TL20R 600x600mm		Silver Grey 60TL21R 600x600mm		Ivory 60TL22R 600x600mm
	Off-white 612TL20URD 600x1200mm		Silver Grey 612TL21URD 600x1200mm		Ivory 612TL22URD 600x1200mm